

Sun Odyssey 379






















Се

Certification conform with CE regulation.	SO 379	SO 409	SO 439
SPECIFICATIONS			
Overall length	11,34 m	12,34 m	13,34 m
Hull length	10,98 m	11,99 m	12,99 m
Waterline length	10,40 m	11,00 m	12,00 m
Beam	3,76 m	3,99 m	4,24 m
Displacement light load with deep draft keel	6700 kg	7860 kg	9640 kg
Standard draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	1,95 m	2,10 m	2,20 m
Standard keel weight	1775 kg	2260 kg	2850 kg
Shoal draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat (double rudders on SO 379)	1,50 m	1,55 m	1,60 m
Shoal keel weight	2039 kg	2470 kg	3150 kg
Swing keel epoxy coated iron keelbox with twin rudders	1,10 - 2,25 m	-	-
Swing keel weight	2313 kg	-	-
CE category	A8 / B9	A9 / BI0	AIO/BII
Architect / designer	M. Lombard	P. Briand	P. Briand
Water rotomolded tank located under forward berth with deck fill	200 L	330 L	330 L
Fuel rotomolded tank located under aft berth with deck fill	130 L	200 L	200 L
Holding tank rotomolded tank located in head compartment with valve for overboard discharge via gravity and deck fitting for pump o	out 80 L	80 L	80 L
Fridge fridge compartment with vertical access	185 L	185 L	185 L
SAILS STANDARD			
Standard mainsail horizontally-cut in high-quality dacron	■ 35 m²	■ 43,5 m²	■ 49,5 m²
Standard headsail 132% horizontally-cut in high-quality dacron	■ 35 m²	-	-
Standard headsail 106% horizontally-cut in high-quality dacron	-	■ 32,5 m²	■ 41,5 m²
Asymmetrical lazy bag in Sunbrella® Taupe fabric with integrated lazy jacks			
Performance Headsail 140% in triradial cut mylar/taffeta laminate	-	□ 46,1 m²	□ 54,7 m²
Performance Headsail 132% in triradial cut mylar/taffeta laminate	□ 35 m²	-	-
Performance Headsail 106% in triradial cut mylar/taffeta laminate	-	□ 32,5 m²	□ 41,5 m²
Self-tacking jib in triradial cut mylar/taffeta laminate	□ 23,3 m²	□ 28,2 m²	□ 35,3 m ²
Performance Mainsail in triradial cut mylar/taffeta laminate	□ 35 m²	□ 43,5 m²	□ 49,5 m²
Inmast furling horizontally-cut in high-quality dacron	□ 27,2 m²	□ 34,2 m²	□ 39,3 m²
Code 0 in triradial cut mylar/aramid laminate	□ 55,2 m ²	□ 70 m²	□ 76,4 m²
Symmetrical spinnaker optimal size for the boat (sail not available)	99 m²	II8 m²	144 m²
Asymmetrical spinnaker optimal size for the boat (sail not available)	90,4 m²	109 m²	133 m²

■ Standard □ Option - Not available

	30 317	SO 409	30 43
SAIL HANDLING			
Genoa winches 2 x Harken 40.2 self-tailing winches	-	-	-
Genoa winches 2 x Harken 46.2 self-tailing winches	-		
Genoa winches 2 x Harken 50.2 self-tailing winches	-		
Coachroof winch Harken 35.2 self-tailing winch to port	•	-	-
Coachroof winch Harken 40.2 self-tailing winches to port	*	•	-
Coachroof winch Harken 35.2 self-tailing with additional winch handle		*	*
Coachroof winch Harken 40.2 self-tailing with additional winch handle	-		
Harken "Rewind" electric genoa winches 2 x 46.2 winches that can sheet-in and sheet-out electrically	-		
Electric coachroof winch 1 x Harken 40.2 12v self-tailing in place of standard winch to port		PREFERENCE	PREFEREN
Genoa tracks adjustable Harken lead cars located on coachroof	-		
Genoa tracks adjustable Harken lead cars (located on the side decks)	-		
Ball-bearing track for self-tacking jib			
Winch handle Harken winch handle with ball-bearing grip	-		
Mainsheet and genoa sheet lead back to helm station with Spinlock jammers		•	
Line jammers Spinlock, on both sides of coachroof with return blocks		•	-
Mainsheet traveller roof-mounted traveller with ball-bearing cars, control lines lead aft to cockpit	*	*	
Spinnaker deck hardware Spinlock jammers Asymmetrical spinnaker gear halyard, 2 sheets, tack line lead forward on deck, Harken blocks	-	-	*
MAST AND RIGGING			
Classic mast aluminium with double spreaders			
Furling mast			
Standing rigging discontinuous 1x19 stainless steel wire	-	•	
Standing rigging discontinuous Dyform® stainless steel wire	A	A	A
Backstay double	-		
Backstay adjustable via mechanical adjuster			
Genoa furler with double slot, attachment to stemhead fitting and furling line lead aft to port helm winch			
Running rigging polyester topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets			
Running rigging Dyneema® mainsail halyard, genoa halyard, mainsheet, genoa sheets	A	A	A
Rigid boom vang with gas cylinder and control line lead aft to the cockpit	*	*	
COCKPIT			
Wood inlay on cockpit bench seating			
Wood cockpit floor inlay	-	_	-
Wood side decks hand-laid wooden side decks			
Cockpit lockers I locker under bench seat and I lazerette locker under the port helm seat			
Cockpit lockers 2 lockers under bench seats and 1 lazerette locker under the port helm seat for technical access to steering system	-		
Liferaft locker located un dedicated compartment between helm seats	90x59x34 cm	90x55x34 cm	90x54x34
Storage compartment for companionway door in forward section of liferaft locker	70237234 (111	70X33X34 CIII	70237237
• , ,		-	-
Storage compartment for companionway door in cockpit locker	-		
Line lockers under helm seats for lines from the primary winches, location for deck fills, cockpit speakers and shorepower inlet			-
Fold down swim platform with telescopic swim ladder	PREFERENCE	-	-
Cockpit table folding table with storage, cup holders, stainless steel handrail, courtesy lighting, 12v plug Solid wood cockpit table with all the same functions of the standard table, but with wooden leaves			
Gas locker located in lazerette locker under starboard helm seat, room for 2 gas bottles with connection to gas system and cut-off valve under stove in the galley			
Wheels 2 leather-covered steering wheels with compasses at each steering position and stainless steel grabrails		_	
Black, composite steering wheels			
Emergency tiller delivered with the boat, chrome fitting in cockpit floor	•	•	
Steering wheel covers Sunbrella® Taupe with zips for easy removal			
Cockpit table cover Sunbrella® Taupe (with or without GPS)			
Instrumentation dedicated space for instruments within easy reach of helm positions, room for GPS chartplotter mounted at aft end of cockpit table with easy viewing from each helm		-	-
Engine controls throttle and engine control panel mounted at starboard helm, engine panel includes, RPM gauge, warning lights, ignition	DD 5550 53 105	BD EN HED E	
Cockpit shower retractable hot and cold water shower with tap	PREFERENCE	PREMIERE	
Cockpit cushions Sunbrella® Taupe cushions for seating area with attachment clips			
Cockpit bimini Sunbrella® Taupe with stainless steel bows, retractable with storage cover			
Cockpit sprayhood wide Sunbrella® Taupe with vinyl windscreen with zip-out middle window for ventilation, retractable			
DECK HARDWARE Anchor locker room for anchor and tackle, integrated windlass area, holder for windlass handle			
Bow pulpit open, stainless steel			- :
Stern pulpits stainless steel with flag holder, buoy bracket		- :	- :
Outboard engine bracket mounted on stern pulpit			
- · · · · · · · · · · · · · · · · · · ·		PREMIERE	
Electric windlass Quick 1000W combination rope and chain, vertical-mounted in the anchor locker, hand-held remote, manual handle Windlass control second windlass control mounted in cockpit with chain counter for easy, short-handed anchoring			
Anchor roller single stainless steel fitting			
Anchor roller single stainless steel fitting with tack point reinforcement	PREMIERE	PREMIERE	PREMIE
· '	_		
Bow platform with telescopic, stainless steel access ladder Aft windlass with folding anchor roller, 10 kg Delta anchor and 50m of line			
Anchoring kit Delta anchor 16kg with 28 meters of 10mm chain and 40 meters of 18mm line Anchoring kit Delta anchor 10kg with 22 meters of 10mm chain and 45 meters of 18mm line			-
Anchoring kit Delta anchor 20kg with 32 meters of 10mm chain and 45 meters of 18mm line			
Lifelines double level of stainless steel lifelines, stainless steel stanchions	DDEEEDENICE	DDEEEDENIGE	DDEEEDE
Lifeline gates opening gates on each side	PREFERENCE	PREFERENCE	PREFERE
Toerail and drainage for side deck		•	
Wood rubrail for hull protection			
Cleats 4 x stainless steel mooring cleats forward and aft	DDEMIEDE	DDEMIEDE	DDEMIE
Midship cleats 2 x stainless steel cleats placed on side deck	PREMIERE	PREMIERE	PREMIE
Mooring kit fenders and docklines Handrails sculpted, long wood handrails on coachroof for secure movement forward			

	SO 379	SO 409	so
TECHNICAL FEATURES AND OPTIONS			
CONSTRUCTION			
Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring		-	-
Hull solid, hand-laid fibreglass, ISO gelcoat surface, protective barrier coat			-
Structure inner fibreglass grid, high-load zones cut out, drainage system through structure	•	-	
Structure 3rd generation inner fibreglass grid, high-load zones cut out and relaminated, drainage system through structure, special emergency repair zone in keel area	-	-	
LIGHTING			
LED navigation lights and anchor light	PREMIERE	PREMIERE	PREM
Flush mounted LED chromed brass ceiling lights in saloon, head compartments and cabins	•	•	
Leather-wrapped LED reading lights in forward cabin and aft cabin (s)	•	•	
Task lighting under side decks in saloon and head compartments	•		DD EFF
Task LED lighting under furniture in saloon	-	PREFERENCE	PREFE
Gooseneck chart light mounted at nav station	•	•	
ELECTRICAL	105.4	105.4	101
12 v alternator output	125 A	125 A	125
Charge distributor/isolator	00.41		
Engine start battery capacity, batteries located under aft berths	80 Ah	110 Ah	110
Domestic battery bank capacity, batteries located under aft berths	80 Ah	230 Ah	230
2 x Extra 80 Ah domestic battery	PREMIERE	- DDEMIEDE	DD E:
2 x Extra 115 Ah domestic battery	-	PREMIERE	PREM
Positive battery switch for engine and domestic bank and general cut-off switch mounted on panel in aft cabin	DDEMIEDE	DDEMIEDE	
Shorepower 220 v inlet with differential breaker, one 220v plug per cabin, 220v plug in galley, saloon and nav station	PREMIERE	PREMIERE	
40 A battery charger, multi-phase	PREMIERE	-	
60 A battery charger, multi-phase	-	PREMIERE	PREM
Inverter 2000 W12v/220v	-	-	
Electrical panel with 12v breakers, 220v breakers, 12v ammeter, 12v consumption meter, 12v charging meter	•	•	
Solar panels on coachroof 2 x 45W with charging relay			
12 v plug per cabin and at nav station		•	
220 v stainless steel microwave, installed in galley cabinet PLUMBING			
Hot and cold pressurised water distributed through-out the boat via semi-rigid hose		=	
"Heavy-duty" water pump and accumulator tank for consistent water pressure			
Hot water tank that is connected to engine heat exchanger and to 230 v electrical system	25 L	40 L	40
Chromed shower faucets in washrooms	•		ı
Electric bilge pump on float switch and manual dual-action pump in the cockpit	•		ı
Extra fresh water tank 130L located under aft starboard berth		-	
Extra fresh water tank 200L located under aft starboard berth	-		
Digital water level display		-	
Shower sumps equipped with individual electric pumps with filters and on-off switches	•	-	
Large manual pump marine toilets	•		
Electric Quiet-Flush toilets in place of standard, available for each head compartment			
80 litre holding tank with gravity drain and deck fitting for forward starboard head (port aft head equipped with standard 80L tank) ENGINE AND STEERING	-		
Yanmar 3YM30 29 HP, 21Kw Sail drive		_	١.
Yanmar 3 H5-CE 40 HP , 29.4 Kw Sail Drive	_		١.
Yanmar 4 H5-CE 54 HP , 39.6 Kw Sail Drive	_	_	
Fully soundproofed engine compartment with engine access behind stairwell and from aft cabin			
Fuel / water separator			
Built-in muffler, forced air ventilation and stainless steel exhaust fitting aft			
Fixed 3-blade propeller		_	
Folding propeller, 3-blade, Flex-o-Fold		_	
Bow thruster 4.3hp/3.2kw installed in a tunnel with dedicated batteries			
Bow thruster 9.5hp/7.1kw installed in a tunnel with dedicated batteries	-		
Fibreglass rudder	•	•	
COMFORT FEATURES AND OPTIONS			
Fixed hull ports	4	8	8
Opening cockpit and roof ports	2	2	1
Lateral fixed windows	6	6	6
Opening ports integrated into lateral windows	2	2	2
Opening deck hatches	4	6	7
Combination shade/insect screens for deck hatches	PREMIERE	PREMIERE	PREM
Simrad audio docking station SonicHub	PREFERENCE	PREFERENCE	PREM
BOSE® 2.1 speaker system ACCOUSTIMASS 3, speakers with base unit in saloon	-	-	PREM
Saloon stereo speakers x 2	PREFERENCE	PREFERENCE	
Cockpit speakers x 2, watertight	PREFERENCE	PREFERENCE	PREM
		1	
	-		_
LED TV 23" mounted on an articulating arm on main saloon bulkhead to port of the forward cabin doorway and DVD player Amplified antenna for TV for masthead mounting	-		
	-		-

Air Conditioning 220 v 32000 BTU I unit installed in the stern, I unit installed in the saloon and I unit installed in the forward cabin, Forced air heating I unit 5500 BTU Webasto® diesel heater installed in stern, vents in aft cabin, saloon and head compartments Forced air heating | unit 5500 BTU + | unit 2000 BTU Webasto® diesel heater installed in stern, vents in aft cabin, saloon and head compartments (only for the 4 cabins version) lacktriangle Performance package * Navigation package * Standard \Box Option - Not available

and aft cabins control panel and thermostat

vents in saloon, head compartments and forward and aft cabins control panel and thermostat

	SO	379		SO				O 43	
INTERIOR FEATURES AND OPTIONS	2C/IH	3C/IH	2C/IH	3C/IH	3C/2H	2C/2H	2C/2H	3C/2H	4C/2F
WOOD									
Fine Teak® interior laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish									
Light oak laminate floorboards									
Laminate floorboards with light-coloured stripes and varnished edges	-	-							
Dark oak laminate floorboards	-	-							
FORWARD CABIN									
Forward owner's cabin with central berth and storage forward of the berth									-
Double berth, with wood trim, high-density foam mattress	2,07 x 1,85 m	2,07 x 1,85 m	2,10 x 2,00 m	2,10 x 2,00 m	2,10 x 2,00 m	2,10 x 2,00 m	2,14 x 2,00 m	2,14 x 2,00 m	-
Deep cabinet with shelves and hanging rod	2	2	2	2	1	I	I	I	-
White vinyl lining on hull with lateral wood shelf									-
Desk/vanity with leatherette lining and fold-up mirror, reading light and chair with backrest	-	-			-	-			-
Private forward head compartment with sink, clothes hook, mirror, towel holder,									
toilet paper holder, cabinet above sink and electric drainage pump	-	-	-	-	•	-			-
Plexiglass folding door for separate shower compartment	-	-	-	-	-	-	PREMIERE	PREMIERE	
Double forward cabins with 2 single bunk berths and forward V-berth	-	-	-	-	-	-	-	-	214 26
Double berth with wood trim, high-density foam mattress	-	-	-	-	-	-	-	-	2,14 x 2,0
Twin single bunks in separate cabin with storage locker	-	-	-	-	-	-	-	-	2,11 x 0,7
Deep cabinet with shelves and hanging rod White vinyl lining on hull with lateral wood shelf	-	-	-	-	-	-	-	-	
Forward head compartment with sink, clothes hook, mirror, towel holder, toilet paper holder, cab	inet	-	-	-	-	-	-	-	-
above sink and electric drainage pump	_	_	_	_	_	_	_	_	
Plexiglass folding door for separate shower compartment		-						_	PREMI
AFT CABIN									11021111
Aft owner's cabin with access to starboard and large berth		_		_	_			_	_
Double berth with high-density foam mattress	2,02 m x 1,94 m	-	2,00 m x 1,78 m	-	-	2,00 m x 1,78 m	2,00 m x 1,85 m	-	-
Deep cabinet with shelves and hanging rod		-		-	-			-	-
White vinyl lining on hull with lateral wood shelf		-		-	-			-	-
Large head compartment aft with sink, clothes hook, mirror, towel holder, toilet paper holder,									
cabinet above sink and electric drainage pump		-		-	-			-	-
Plexiglass folding door for separate shower compartment	PREMIERE	-	PREMIERE	-	-	PREMIERE	PREMIERE	-	-
Stainless steel hanging bar	-							-	-
Locker and technical compartment with double access from cockpit and through head with 2 storage baskets and lighting		-		-	-			-	-
Twin aft cabins	-		-			-	-		
Double berths, high-density foam	-	2,02 m x 1,58 m	-	2,00 m x 1,57 m	2,00 m x 1,57 m	-	-	2,00 m x 1,60 m	2,00 m x l
Deep cabinet with shelves and hanging rod per cabin	-		-			-	-		
White vinyl lining on hull with lateral wood shelf	-		-	-		-	-		-
Head compartment aft with sink, separate shower, clothes hook, mirror, towel holder,									
toilet paper holder, cabinet above sink, electric drainage pump, access from saloon	-	•	-	-	•	-	-		-
Stainless steel hanging bar	-	DDEMIEDE	-	DDEMIEDE	DDEMIEDE	-		- DD FMIFDE	- DD EMI
Plexiglass folding door for separate shower compartment	-	PREMIERE	-	PREMIERE	PREMIERE	-	-	PREMIERE	PREMI
NAVIGATION STATION Novigation station full function with general electrical cond and be already		_	_					_	_
Navigation station full-function with general electrical panel and bookshelf			-						-
Central nav desk with leatherette lining and interior storage Hanging locker		-	-	-	-	-	-	-	-
SALOON	-	-	-	-	-	-	-	-	-
Saloon with U-shaped seating area to starboard, wrap-around cushions and storage under seating area									
Saloon dining table with wood fiddles, removable pedestal legs									
Luxury saloon table with folding leaves and central bar cabinet			-	-		_			_
Luxury salon table with central bar unit, folding top, and sliding tracks to transform into double berth		-							
Saloon berth conversion kit									
Storage cabinets along hull sides									
Lounge seating to port with plush cushions and upper storage cabinets									
2 removable stools for saloon with tie-down kit	-	-							
Companionway with wood steps and non-slip strips									-
Plexiglass companionway door with dedicated storage location						-			
GALLEY									
Galley with double stainless steel sinks with covers, solid countertops, chrome plumbing fittings, storage cabinets and drawers									
L-galley to port with glass separator between galley counter and seating area	-					-	-		
Storage compartment for books and magazines built into the galley façade									-
Gimballed 2-burner stove with oven with stainless steel protection bar									
Luxury 2-burner stove with black finish, wood handle, stainless steel oven/broiler			PREMIERE			PREMIERE		PREMIERE	
					DD FFFD F LOF	DD FFFD FA LOF	DD FFFD FA LOF	DD FFFD FA LOF	2025550
Single fridge box with freezer area, wire baskets, 12v refrigeration and integrated compressor		DD FFFFF F			. DOLLED CALCE	I PRIFFERENCE	PKEFERENCE	PREFERENCE	PREFERE
Single fridge box with freezer area, wire baskets, 12v refrigeration and integrated compressor Vertical fridge door		PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE	TIVELENCIACE			
Vertical fridge door		PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE	TREFERENCE			
Vertical fridge door H E A D R O O M	PREFERENCE		PREFERENCE			THEFENCE		1.00	
Vertical fridge door H E A D R O O M Forward cabin	PREFERENCE	I,84 m	PREFERENCE	1,8	4 m	TREFERE		1,88 m	
Vertical fridge door H E A D R O O M Forward cabin Aft cabin (s)	PREFERENCE 1,80 / 1,90	I,84 m 0 m	PREFERENCE	1,8 [,]	4 m 5 m	TREFERENCE		1,97 m	
Vertical fridge door H E A D R O O M Forward cabin	1,80 / 1,90	I,84 m	PREFERENCE	1,8 [,] 1,9 [,]	4 m	TREFERENCE			



■ Standard □ Option - Not available

C = Cabins H = Head

