



SPECIFICATIONS

FourStroke: 80-115 hp



HP / kW	100 / 74
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	2.1
Full throttle RPM	5000-6000
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	Unleaded 90RON minimum
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Compatible Dual cable mechanical Hydraulic power steering
Shaft length	20" / 508 mm 25" / 635 mm
Gearcase ratio	2.38:1
Dry weight *Lightest model available	165 kg
CARB star rating	3
Bore and stroke	3.5 x 3.2" / 90 x 81 mm
Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)

Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Command Thrust
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Color	Phantom Black
Lubrication system	Wet sump
Oil Capacity	5.5 qts / 5.2 l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	70° (-6° to 64°)

© 2017 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.