



SPECIFICATIONS

FourStroke: 40-60 hp



HP / kW	50 / 37
Engine type	Inline 4
Displacement (CID/CC)	60.8 / 995
Full throttle RPM	5500-6000
Fuel induction system	2 valves per cylinder, single overhead cam (SOHC)
Alternator amp / Watt	18 amp / 226 watt
Recommended fuel	Unleaded 90RON minimum
Recommended oil	Mercury FourStroke 25W40 Marine Oil
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Electric (turn-key)
Steering	Big Tiller Compatible Remote Tiller Kit
Shaft length	20" / 508 mm
Gearcase ratio	1.83:1
Dry weight *Lightest model available	112 kg
CARB star rating	3
Bore and stroke	2.56 x 2.95" / 65 x 75 mm
Ignition	ECM 70
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat
Gear shift	F-N-R
Gearcase options	Standard

Trim system	Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Remote fuel tank (optional)	Yes
Color	Phantom Black
Lubrication system	Wet sump
