



## SPECIFICATIONS

### FourStroke: 40-60 hp



<b>HP / kW</b>	60 / 44.1
<b>Engine type</b>	Inline 4
<b>Displacement (CID/CC)</b>	60.8 / 995
<b>Full throttle RPM</b>	5500-6000
<b>Fuel induction system</b>	2 valves per cylinder, single overhead cam (SOHC)
<b>Alternator amp / Watt</b>	18 amp / 226 watt
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Recommended oil</b>	Mercury FourStroke 25W40 Marine Oil
<b>Engine protection operator warning system</b>	SmartCraft Engine Guardian
<b>Compatible with SmartCraft digital technology</b>	Yes
<b>Starting</b>	Electric (turn-key)
<b>Steering</b>	Big Tiller Compatible Remote Tiller Kit
<b>Shaft length</b>	20" / 508 mm
<b>Gearcase ratio</b>	1.83:1
<b>Dry weight *Lightest model available</b>	112 kg
<b>CARB star rating</b>	3
<b>Bore and stroke</b>	2.56 x 2.95" / 65 x 75 mm
<b>Ignition</b>	ECM 70
<b>Fuel system</b>	Electronic Fuel Injection (EFI)
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Standard

<b>Trim system</b>	Power Trim
<b>Exhaust system</b>	Through prop
<b>Shallow water trim range (degrees)</b>	20
<b>Remote fuel tank (optional)</b>	Yes
<b>Color</b>	Phantom Black
<b>Lubrication system</b>	Wet sump

---