



SPECIFICATIONS

FourStroke: 80-115 hp



HP / kW	80 / 59.2
Engine type	8-valve single overhead cam (SOHC) Inline 4
Displacement (L)	2.1
Full throttle RPM	4500-5500
Air induction	Performance-Tuned Scroll Intake Manifold
Fuel induction system	Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt	35 amp / 441 watt with water-cooled voltage regulator
Recommended fuel	Unleaded 90RON minimum
Recommended oil	Mercury FourStroke Oil 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes
Starting	Smart Start Electric
Controls	Mechanical throttle & shift
Steering	Big Tiller Compatible Dual cable mechanical Hydraulic power steering
Shaft length	20" / 508 mm
Gearcase ratio	2.07:1
Dry weight *Lightest model available	163 kg
CARB star rating	3
Bore and stroke	3.5 x 3.2" / 90 x 81 mm
Ignition	SmartCraft ECM 70 Digital Inductive
Fuel system	Electronic Fuel Injection (EFI)
Cooling system	Water-cooled with thermostat

Gear shift	F-N-R
Gearcase options	Standard
Trim system	Power Tilt Power Trim
Exhaust system	Through prop
Shallow water trim range (degrees)	20
Color	Phantom Black
Lubrication system	Wet sump
Oil Capacity	5.5 qts / 5.2 l
Maximum Trim Range	22° (-6° to 16°)
Maximum Tilt Range	70° (-6° to 64°)

© 2017 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.