



SPECIFICATIONS

FourStroke: 25-30 hp



| | |
|--|--|
| HP / kW | 25 / 18.6 |
| Engine type | Inline 3 |
| Displacement (CID/CC) | 32.1 / 526 |
| Full throttle RPM | 5000-6000 |
| Fuel induction system | 2 valves per cylinder, single overhead cam (SOHC) |
| Alternator amp / Watt | 15 amp / 186 watt |
| Recommended fuel | Unleaded 90RON minimum |
| Recommended oil | Mercury FourStroke Oil 10W-30 |
| Engine protection operator warning system | Low oil pressure Over-rev Overheat Sensor failure |
| Starting | Electric (turn-key) Manual |
| Steering | Remote Tiller |
| Shaft length | 15" / 381 mm 20" / 508 mm |
| Gearcase ratio | 1.92:1 |
| Dry weight *Lightest model available | 71 kg |
| CARB star rating | 3 |
| Bore and stroke | 2.40 x 2.36" / 61 x 60 mm |
| Ignition | CDI w/electronic spark advance |
| Fuel system | Electronic Fuel Injection (EFI) |
| Cooling system | Water-cooled with thermostat |
| Gear shift | F-N-R |
| Gearcase options | Standard |
| Trim system | Manual Power Trim |

| | |
|--|---------------|
| Exhaust system | Through prop |
| Shallow water trim range (degrees) | 16 |
| Remote fuel tank standard (gal / L) | 6.6 / 25 |
| Color | Phantom Black |
