



## SPECIFICATIONS

### FourStroke: 25-30 hp



<b>HP / kW</b>	30 / 22.4
<b>Engine type</b>	Inline 3
<b>Displacement (CID/CC)</b>	32.1 / 526
<b>Full throttle RPM</b>	5250-6250
<b>Fuel induction system</b>	2 valves per cylinder, single overhead cam (SOHC)
<b>Alternator amp / Watt</b>	15 amp / 186 watt
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Recommended oil</b>	Mercury FourStroke Oil 10W-30
<b>Engine protection operator warning system</b>	Low oil pressure Over-rev Overheat Sensor failure
<b>Starting</b>	Electric (turn-key) Manual
<b>Steering</b>	Remote Tiller
<b>Shaft length</b>	15" / 381 mm 20" / 508 mm
<b>Gearcase ratio</b>	1.92:1
<b>Dry weight *Lightest model available</b>	78 kg
<b>CARB star rating</b>	3
<b>Bore and stroke</b>	2.40 x 2.36" / 61 x 60 mm
<b>Ignition</b>	CDI w/electronic spark advance
<b>Fuel system</b>	Electronic Fuel Injection (EFI)
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Standard
<b>Trim system</b>	Gas assist Power Trim

---

<b>Exhaust system</b>	Through prop
<b>Shallow water trim range (degrees)</b>	16
<b>Remote fuel tank standard (gal / L)</b>	6.6 / 25
<b>Color</b>	Phantom Black

---



## SPECIFICATIONS

### FourStroke: 25-30 hp



<b>HP / kW</b>	30 / 22
<b>Engine type</b>	Inline 3
<b>Displacement (CID/CC)</b>	747
<b>Full throttle RPM</b>	5500 - 6000
<b>Alternator amp / Watt</b>	18 amp / 226 watt
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Starting</b>	Electric
<b>Steering</b>	Big Tiller Remote
<b>Shaft length</b>	20" / 508 mm
<b>Gearcase ratio</b>	2.00:1
<b>Dry weight *Lightest model available</b>	98 kg
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Command Thrust