



## SPECIFICATIONS

### FourStroke: 4-6 hp



<b>HP / kW</b>	4 / 2.9
<b>Engine type</b>	1 cylinder
<b>Displacement (CID/CC)</b>	7.5 / 123
<b>Full throttle RPM</b>	4500-5500
<b>Fuel induction system</b>	2-valve pushrod (overhead valve)
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Recommended oil</b>	Mercury FourStroke Oil 10W-30
<b>Engine protection operator warning system</b>	Low oil pressure Over-rev
<b>Starting</b>	Manual
<b>Steering</b>	Tiller
<b>Shaft length</b>	15" / 381 mm 20" / 508 mm
<b>Gearcase ratio</b>	2.15:1
<b>Dry weight *Lightest model available</b>	25 kg
<b>CARB star rating</b>	3
<b>Bore and stroke</b>	2.32 x 1.77" / 59 x 45 mm
<b>Ignition</b>	CDI w/electronic spark advance
<b>Fuel system</b>	Carbureted
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Standard
<b>Trim positions</b>	6
<b>Exhaust system</b>	Through prop
<b>Shallow water drive</b>	Yes
<b>Shallow water trim</b>	16

<b>range (degrees)</b>	
<b>Integrated fuel tank (gal / L)</b>	0.3 / 1.1
<b>Optional fuel tank (gal / L)</b>	3.2 / 12
<b>Color</b>	Phantom Black

© 2017 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.