



## SPECIFICATIONS

### FourStroke: 8-9.9 hp



<b>HP / kW</b>	9.9 / 7.3
<b>Engine type</b>	Inline 2
<b>Displacement (CID/CC)</b>	12.8 / 208
<b>Full throttle RPM</b>	5000-6000
<b>Fuel induction system</b>	2 valves per cylinder, single overhead cam (SOHC)
<b>Alternator amp / Watt</b>	6 amp / 76 watt
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Recommended oil</b>	Mercury FourStroke Oil 10W-30
<b>Engine protection operator warning system</b>	Low oil pressure Over-rev
<b>Starting</b>	Electric Manual
<b>Steering</b>	Remote Tiller
<b>Shaft length</b>	15" / 381 mm 20" / 508 mm
<b>Gearcase ratio</b>	2.08:1
<b>Dry weight *Lightest model available</b>	38 kg
<b>CARB star rating</b>	3
<b>Bore and stroke</b>	2.16 x 1.73" / 55 x 44 mm
<b>Ignition</b>	CDI w/electronic spark advance
<b>Fuel system</b>	Carbureted
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Standard
<b>Trim system</b>	Power Tilt
<b>Trim positions</b>	Ratcheting

---

<b>Exhaust system</b>	Through prop
<b>Shallow water drive</b>	Yes
<b>Shallow water trim range (degrees)</b>	16
<b>Integrated fuel tank (gal / L)</b>	3.2 / 12
<b>Remote fuel tank standard (gal / L)</b>	3.2 / 12
<b>Color</b>	Phantom Black

---



## SPECIFICATIONS

### FourStroke: 8-9.9 hp



<b>HP / kW</b>	9.9 / 7.3
<b>Engine type</b>	Inline 2
<b>Displacement (CID/CC)</b>	12.8 / 208
<b>Full throttle RPM</b>	5000-6000
<b>Fuel induction system</b>	2 valves per cylinder, single overhead cam (SOHC)
<b>Alternator amp / Watt</b>	6 amp / 76 watt
<b>Recommended fuel</b>	Unleaded 90RON minimum
<b>Recommended oil</b>	Mercury FourStroke Oil 10W-30
<b>Engine protection operator warning system</b>	Low oil pressure Over-rev
<b>Starting</b>	Electric Manual
<b>Steering</b>	Remote Tiller
<b>Shaft length</b>	15" / 381 mm 20" / 508 mm
<b>Gearcase ratio</b>	2.08:1
<b>Dry weight *Lightest model available</b>	38 kg
<b>CARB star rating</b>	3
<b>Bore and stroke</b>	2.16 x 1.73" / 55 x 44 mm
<b>Ignition</b>	CDI w/electronic spark advance
<b>Fuel system</b>	Carbureted
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Gearcase options</b>	Standard
<b>Trim system</b>	Power Tilt
<b>Trim positions</b>	Ratcheting

---

<b>Exhaust system</b>	Through prop
<b>Shallow water drive</b>	Yes
<b>Shallow water trim range (degrees)</b>	16
<b>Integrated fuel tank (gal / L)</b>	3.2 / 12
<b>Remote fuel tank standard (gal / L)</b>	3.2 / 12
<b>Color</b>	Phantom Black

---