



Certification conform with CE regulation.

	SO 30i	SO 30i Performance	SO 33i	SO 33i Performance
SPECIFICATIONS				
Overall length	8,99 m	8,99 m	9,96 m	9,96 m
Hull length	8,79 m	8,79 m	9,74 m	9,74 m
Waterline length	8,26 m	8,26 m	9,16 m	9,16 m
Beam	3,18 m	3,18 m	3,34 m	3,34 m
Displacement light load with deep draft keel	3945 kg	3945 kg	4645 kg	4645 kg
Standard draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	1,75 m	1,75 m	1,90 m	1,90 m
Standard keel weight	946 kg	946 kg	1500 kg	1500 kg
Shoal draft cast iron fin keel with elongated bulb and exterior epoxy barrier coat	-	-	1,47 m	-
Shoal keel weight	-	-	1695 kg	-
Swing keel version galvanised centreboard located in an external iron keel fin	0,85-2,00 m	-	0,85-2,20 m	-
Swing keel weight	1039 kg	-	1516 kg	-
Air Clearance measured from waterline to top of the mast	13,91m	14,40 m	15,16 m	15,46 m
CE category (*swing keel version of Sun Odyssey 30i with furling mast C6 - swing keel version of Sun Odyssey 33i B6)	B6*	B6	A6 / B8*	A6 / B8
Architect/designer	M. Lombard	M. Lombard	M. Lombard	M. Lombard
Water capacity	160 L	160 L	160 L	160 L
Fuel rotomolded tank located under aft berth with deck fill	50 L	50 L	140 L	140 L
Holding tank rotomolded tank located in head compartment with valve for overboard discharge via gravity and deck fitting for pump out	85 L	85 L	85 L	85 L
Fridge compartment with vertical access	100 L	100 L	100 L	100 L
SAILS				
Classic mainsail 80% battened, polyester sailcloth, Rutgerson® stainless steel eyes and 2 reinforced reef points with auto reef	■ 22,2 m²	-	■ 26,5 m²	-
Furling genoa 115% high-tenacity Dacron cloth, UV luff protection, Rutgerson® stainless steel eyes	■ 20,8 m²	-	■ 25 m²	-
Performance mainsail , semi-full batten, Prestige series tri-radial with sandwich construction of double taffeta layers and Mylar for form stability, 2 automatic reefs	-	■ 23,4 m²	-	■ 27,6 m²
Performance furling genoa tri-radial Prestige series with sandwich constructions of double taffeta layers and Mylar for form stability and UV luff protection, Rutgerson® stainless steel eyes	-	■ 20,8 m²	-	■ 27,7 m²
Self-tacking jib horizontally-cut in high-quality dacron, UV luff protection, Rutgerson® stainless steel eyes	□ 13,6 m²	-	□ 17,9 m²	-
Furling mainsail polyester sailcloth, UV luff protection, Rutgerson® stainless steel eyes	□ 21,5 m²	-	□ 25,7 m²	-
Spinnaker optimal size for boat (not available from Jeanneau)	75 m²	75 m²	100 m²	100 m²
Total sail area for standard mast and sails	43 m²	44,2 m²	51,5 m²	55,3 m²

■ Standard □ Option - Not available

		SO 30i	SO 30i Performance	SO 33i	SO 33i Performance
■	SAIL HANDLING				
	Lazy bag in Sunbrella® Taupe fabric with integrated lazy jacks	■	■	■	■
	Genoa winches 2 x Harken 35.2 self-tailing winches	■	-	■	-
	Coachroof winch 1 x Harken 20.1 self-tailing winch	■	-	■	-
	Coachroof winch 1 x Harken 35.2 self-tailing winch	-	■	-	■
	Genoa winches 2 x Harken 40.2 self-tailing winches	-	■	-	■
	Genoa tracks adjustable lead cars	■	-	■	-
	Turning blocks for genoa sheets	■	■	■	■
	Harken genoa tracks ball-bearing cars with control lines lead aft to cockpit	-	■	-	■
	Winch handle 1 x Harken handle with ball-bearing grip	■	■	■	■
	Line jammers Spinlock, on coachroof	■	■	■	■
	Mainsheet attached to padeye in cockpit for easy use and can be removed when in port	■	-	-	-
	Mainsheet attached to padeyes forward of companionway hatch with sheet lead back to cockpit winch	-	-	■	-
	Mainsheet traveller cockpit-mounted Harken traveller with ball-bearing cars and fine tune	-	■	-	■
	Spinnaker deck hardware 2 x jammers on coachroof, 3-sheave return block on deck, padeyes on side decks	PREMIERE	PREMIERE	PREMIERE	PREMIERE
	Asymmetrical spinnaker gear halyard, 2 sheets, tack line lead forward on deck, 3 blocks	□	□	□	□
	Symmetrical spinnaker gear halyard, 2 sheets, pole uphaul and downhaul, spinnaker pole, and necessary blocks	□	□	□	□
■	MAST AND RIGGING				
	Selden classic mast aluminium with double spreaders, deck-stepped	■	-	■	-
	Selden performance classic mast aluminium with double spreaders, 9/10th fractional	-	■	-	■
	Standing rigging discontinuous 1x19 stainless steel wire	■	■	■	■
	Backstay fixed	■	-	■	-
	Backstay adjustable via a block and tackle system 1:16	-	■	-	■
	Genoa furler with attachment to stemhead fitting and furling line lead aft to roof winch	■	-	■	-
	Genoa furler racing series with removable drum, double sail slot, furling line lead aft to roof winch	-	■	-	■
	Running rigging topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets	■	-	■	-
	Dyneema® Running rigging mainsail halyard, genoa halyard, mainsheet with fine tune, genoa sheets, polyester boom topping lift	-	■	-	■
	Boom vang block and tackle system	■	-	■	-
	Rigid boom vang with gas cylinder and control line lead aft to the cockpit	-	■	-	■
	Anchor light and tricolour at masthead, steaming light and bicolour running light on leading edge of the mast	■	■	■	■
■	COCKPIT & DECK STORAGE				
	Wood inlay on cockpit bench seating	■	■	■	■
	Wood cockpit floor inlay	□	□	□	□
	Wood side decks	-	-	□	□
	Cockpit locker 1 large cockpit locker to starboard under bench seat and separate gas locker on stern	■	■	■	■
	Liferaft locker located in dedicated compartment in stern	35x56x92 cm	35x56x92 cm	35x56x92 cm	35x56x92 cm
	Cockpit table removable on aluminium base (tiller version)	□	□	-	-
	Cockpit table large folding table mounted on stainless steel base	-	-	PREMIERE	-
	Cockpit table folding table mounted on pedestal	□	□	-	PREMIERE
	Tiller varnished wood tiller with extension handle, folds out of the way to keep cockpit clear	■	■	-	-
	Wheel leather-covered steering wheel mounted on steering pedestal with grabrail and pod for instrumentation	□	□	■	■
	Folding steering wheel (included in wheel option for SO30i)	□	□	□	□
	Compass	■	■	■	■
	Transom seat folding seat for easy access to the transom	■	■	■	■
	Engine controls throttle and engine control panel, warning lights, ignition protected by a plexiglass panel	■	■	■	■
	Swim ladder stainless steel folding ladder mounted on transom step	■	■	■	■
	Cockpit shower retractable cold water shower with tap	PREFERENCE	PREFERENCE	-	-
	Cockpit shower retractable hot and cold water shower with tap	-	-	PREFERENCE	PREFERENCE
	Cockpit cushions Sunbrella® Sling Taupe cushions for seating area with attachment clips	□	□	□	□
	Cockpit sprayhood wide Sunbrella® Taupe with vinyl windscreen	□	□	□	□
	Cockpit bimini Sunbrella® Taupe with stainless steel bows, retractable with storage cover	□	□	□	-
	Anchor locker forward, room for anchor and tackle	■	■	■	■
■	DECK HARDWARE				
	Bow pulpit stainless steel	■	■	■	■
	Stern pulpits stainless steel with buoy bracket	■	■	■	■
	Outboard engine bracket mounted on stern pulpit	□	□	□	□

■ Standard □ Option - Not available

	SO 30i	SO 30i Performance	SO 33i	SO 33i Performance
Windlass 700 W combination rope and chain 8 mm, vertical-mounted in the anchor locker, hand-held remote, manual handle	□	□	-	-
Windlass 1000 W combination rope and chain 10 mm, vertical-mounted in the anchor locker, hand-held remote, manual handle	-	-	□	□
Anchor roller single roller	■	■	■	■
Anchoring kit fluke anchor 14 kg with 23 meters of 8 mm chain and 35 meters of 14 mm line	□	□	-	-
Anchoring kit fluke anchor 16 kg with 28 meters of 10 mm chain and 40 meters of 18 mm line	-	-	□	□
Lifelines double level of stainless steel lifelines, stainless steel stanchions	■	■	■	■
Toerail	■	■	■	■
Cleats 4 x aluminium mooring cleats forward and aft	■	■	■	■
Midship cleats	-	-	PREMIERE	PREMIERE
Mooring kit fenders and docklines	□	□	□	□
Handrails sculpted, long wood handrails on coachroof for secure movement forward	■	■	■	■
TECHNICAL FEATURES AND OPTIONS				
CONSTRUCTION				
Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring	■	■	■	■
Hull solid, hand-laid fibreglass, ISO glecoat surface, protective barrier coat	■	■	■	■
Structure inner fibreglass grid, high-load zones cut out, drainage system through structure	■	■	■	■
LIGHTS				
Flush mounted chromed brass LED ceiling lights in saloon and cabins	■	■	■	■
Reading lights in cabins	■	■	■	■
Gooseneck chart light mounted at nav station	■	■	■	■
ELECTRICAL				
12v alternator output	80 A	80 A	80 A	80 A
Battery 70 Ah for domestic bank with charge distributor/isolator	PREMIERE	PREMIERE	■	■
Extra 70 Ah for domestic battery	-	-	PREMIERE	PREMIERE
Engine start/domestic battery capacity	70 Ah	70 Ah	70 Ah	70 Ah
Battery switches for engine bank, positive battery switch for domestic bank (when option is fitted) and negative general cut-off switch	■	■	■	■
220 v shore power inlet with differential breaker, one 220 v plug per cabin, galley and saloon + 25 A Cristec charger	PREMIERE	PREMIERE	PREMIERE	PREMIERE
PLUMBING				
Pressurised water distributed through-out the boat via semi-rigid hose	■	■	■	■
“Heavy-duty” water pump and accumulator tank for consistent water pressure	■	■	■	■
25 litres hot water tank that is connected to engine heat exchanger and 220v system (when 220 v shorepower system fitted)	PREMIERE	PREMIERE	■	■
Manual bilge pump in the cockpit	■	■	■	■
Chromed shower faucets in washroom	■	■	■	■
Shower sumps equipped with individual electric pumps with filters and on-off switches	■	■	■	■
Manual pump marine toilets	■	■	■	■
ENGINE				
Yanmar 3YM20 21 HP , 15.3 Kw with heat exchanger, latest generation of environmentally friendly engines	■	■	■	■
Fully soundproofed engine compartment with engine access behind stairwell and from aft cabin	■	■	■	■
Stainless steel propeller shaft 25 mm diameter and maintenance free stuffing box	■	■	■	■
Fuel/water separator	■	■	■	■
Built-in muffler, air ventilation and stainless steel exhaust fitting aft	■	■	■	■
Fixed 3-blade bronze propeller	■	-	■	-
Folding 3-blade propeller	-	■	□	■
COMFORT FEATURES AND OPTIONS				
Fixed windows along coachroof with integrated opening ports	■	■	■	■
Pleated curtain kit with integrated insect screens for hatches	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
Opening cockpit and roof ports	2	2	2	2
Opening cockpit port into aft cabin	1 x PREMIERE	1 x PREMIERE	2 x PREMIERE	2 x PREMIERE
Opening deck hatch in saloon	■	■	■	■
Opening deck hatch in forward cabin	■	■	■	■
Opening deck hatch in aft cabin	■	■	■	■
Audio docking station Sonichub Simrad with remote and 2 speakers in saloon	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
Cockpit speakers watertight	PREFERENCE	PREFERENCE	PREFERENCE	PREFERENCE
Forced air heating 1 unit 3900 BTU Webasto® diesel heater installed in cockpit lazerette, vents in forward cabin, aft cabin and saloon	-	-	□	□
■ Standard □ Option - Not available				

		SO 30i 2C/H	SO 33i 2C/H
INTERIOR FEATURES AND OPTIONS			
WOOD			
Fine Teak® laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish		■	■
Laminate floorboards laminated floorboards with light-coloured lines and sealed edges		■	■
FORWARD CABIN			
Forward cabin with V-berth		■	■
Double berth with high-density foam mattress		2,1 x 1,82 m	2 x 1,80 m
Storage locker under berth		■	■
Cabinet with hanging rod		■	■
Storage cabinet with shelves		-	■
Wide, bi-fold door for easy access		■	■
Vinyl lining on hull with lateral wood shelf		■	■
Reading light		■	■
AFT CABIN			
Aft cabin		■	■
Double berth with high-density foam mattress		1,92 m x 1,40 m	2,10 x 2 m
Deep cabinet with shelves and hanging rod		■	■
Vinyl lining on hull with lateral wood shelf		■	■
Leather storage organiser		PREFERENCE	PREFERENCE
Reading light		■	■
HEAD			
Head compartment accessible from saloon with sink, storage cabinet, clothes hook, towel holder, toilet paper holder, shower sump with electric drainage pump		■	■
Wet locker		■	■
NAVIGATION STATION			
Navigation station		■	■
Full-featured electrical panel with spare breakers, voltmeter and 12v plug		■	■
Sliding nav desk that can be placed in forward-facing or aft-facing position for increased seating with storage underneath		-	■
Aft-facing nav station, seating on bench seat		■	-
Navigation desk with storage		■	■
SALOON			
Saloon with seating, cushions and storage under seating area		■	■
Folding saloon table with fiddles		■	■
Bottle storage compartment in table with leather cover		■	■
Cushion to fit under nav desk to convert portside settee to single berth		□	PREFERENCE
Upper storage cabinets		■	■
Companionway with 4 varnished wood steps		■	■
GALLEY			
Galley with laminated countertops, chrome plumbing fittings, storage cabinets		■	■
L-galley to starboard with round stainless steel sink 100 L, icebox and cutlery storage		■	■
Leather storage organiser		PREFERENCE	PREFERENCE
12v compressor under stove with evaporator plate located in fridge compartment		PREMIERE	■
2-burner stove (for Sun Odyssey 33i this stove is used when microwave option is ordered)		■	□
Gimballed 2-burner stainless steel with oven with stainless steel protection bar (not compatible with microwave option)		□	■
Microwave oven (not compatible with oven option)		□	□
Luxury 2-burner stove with black finish, wood handle, stainless steel oven/broiler		-	□
HEAD ROOM			
Forward cabin		1,83 m	1,86 m
Aft cabin		1,90 m	1,89 m
Companioway		1,87 m	1,88 m
Saloon		1,82 m	1,85 m
Galley		1,87 m	1,89 m

■ Standard □ Option - Not available C = Cabins H = Head



JEANNEAU

Ets JEANNEAU - BP 529 - 85505 LES HERBIERS CEDEX - FRANCE - TEL +33 (0)2 51 64 20 20 - FAX +33 (0)2 51 67 37 65

INTERNET : <http://www.jeanneau.com>

