

SPECIFICATIONS



Overall length	14,42 m / 47'3"	CE category 4
Overall Length with Bowsprit	14,80 m / 48'6"	Fuel capacity
Hull length	14,00 m / 45'11"	Water capacity
Waterline length	13,24 m / 43'5"	Fridge capacity
Beam	4,49 m / 14'8"	Holding tank c
Displacement light load with deep draft keel	11290 kg / 24890 lbs	Architect / Des
Standard keel draft	2,24 m / 7'4"	Standard mains
Standard keel weight	2870 kg / 6327 lbs	Polyester High
Shoal keel draft	1,65 m / 5'4"	Standard 125 %
Shoal keel weight	3213 kg / 7083 lbs	in Polyester Hig
CE category 2-3 cabins layout	A9 / B10 / C14	

CE category 4-5 cabins layout	A13 / B14 / C16
Fuel capacity	240 L / 63 US gal
Water capacity	640 L / 169 US gal
Fridge capacity	190 L / 50 US gal
Holding tank capacity	130 L / 34 US gal
Architect / Designer	Philippe Briand Piaton Bonet Yacht Design Jeanneau Design
Standard mainsail, horizontally-cut, in Polyester High Strength	56,60 m² / 609 Sq ft
Standard 125 % headsail, horizontally-cut, in Polyester High Strength	53,60 m² / 577 Sq ft

AN EXCEPTIONAL LEVEL OF EQUIPMENT

EXTERIOR

Sailing features

• High aspect ratio rig, cathedral mast and split rigging

- Harken genoa tracks
- Harken roof and primary winches
- Harken deck hardware
- Anodised aluminium mast and boom
- Boom with rigid boom vang and lowered gooseneck, to ease manoeuvring
- Battened mainsail. Furling genoa with UV protection
 Discontinuous standing rigging, stainless steel wire
- Lazy bag and lazy jacks
- Sheets lead back to the helm German sheeting
- Large choice of sails sets and optional performance mast

Construction

- Infused sandwich hull with balsa core and fiberglass skins, ISO gelcoat surface, protective barrier coat
- Infused fiberglass inner liner, easy access to grounding frame, relamination in stays attachment areas.
- Prisma Process® injected deck, ISO gelcoat, discontinuous balsa block coring - 30 % weight savings as compared to traditional decks
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation

Cockpit

- Asymmetrical cockpit with dedicated area for dinning, lounging and manoeuvring
- Walk-in access to side decks, enabling to walk around the deck without crossing any steps
- Multi-function cockpit table
- Leather-covered stainless steel steering wheels
- Large aft fold-down swim platform with telescopic ladder • Hinged companionway doors

- Deck
- · Easy circulation thanks to the inclined side decks
- Flush deck hatches
- Long tinted acrylic roof windows
- Split rigging: Inboard shrouds for easier access forward
- External woodwork and inlays made of Teak
- Mid-ship cleats
- Electric windlass

INTERIOR

- One-level interior with no door sills
- Large doors, double access to aft head
- Leather-wrapped handrails
- LED lighting
- Large, rectangular double berths
- Fully-upholstered hull sides
- Blinds for each hatch and opening in the forward and aft
- cabins
- Numerous choices of interior ambiances
- Large seaworthy storage spaces, with fiddles. Soft closing drawers and cabinets
- · Separated shower compartment in the forward owner's cabin
- Full-size mirrors in the owner's cabin and in the heads

Chart table

 Large navigation desk with leatherette lining and interior storage for a portable computer, electrical panel, sofa and wide books storage

Galley

• U-shape galley, ideally located near the centre of gravity of the boat

- Corian® countertops
- Double stainless steel sinks
- 2-burner stove with oven
- Fridge 130 L / 34 US gal with top access to better maintain the cold air

Woodwork

- Woodwork in Alpi® Teak or Grey Cedar
- UV stabilized varnish
- Laminate floorboard in Ceruse Oak colour • Numerous solid wood mouldings

TECHNICAL

- Electrical
- LED navigation and anchoring lights
- 12 V electrical panel
- Battery Exide Dual Marine
- 125 A alternator and charge distributor/isolator
- Positive and negative battery cut-off switches to better protect battery banks

Water System

- Hot and cold cockpit shower
- Hot water heater 40 L / 11 US gal
- "Heavy-duty" water pump

Engine

- Latest-generation Yanmar 57 HP Common Rail Sail Drive engine with reduced CO² emissions and consumption
- Fixed 3-blade propeller
- Sound insulation 40 mm / 1 1/2" thick, with fire retardant film

TRIM LEVELS AND PACKAGE

		PREMIERE	PREFERENCE
	Layout applicable	A, B, C	A, B
GRP bowsprit with integrated anchor roller (replaces the standard anchor roller)		~	v
Second windlass control with chain counter, installed in the cockpit		~	~
Halyard bags in the cockpit with stainless steel frame (3)		~	<i>~</i>
40 A battery charger for 12 V battery banks		~	~
60 A battery charger for 12 V battery banks		~	~
Additional service batteries 3 x 115 Ah		~	¥
LED courtaisy lighting in the cockpit		~	~
3 burner cooker and oven with grill function (replaces standard 2 burner cooker)		~	¥
Protective GRP eyebrow for the long acrylic roof windows		~	¥
Navicolor battery monitoring		~	¥
Upholstered bulkheads			¥
Indirect LED lighting, and lamps on bulkheads			¥
Sound deadening lining in cabinets			~
Shades for windows and ports in the saloon			¥
Shades and screens for hatches in the saloon			~
Signature clock and barometer set at the chart table			~
Vertical door fridge			~
Specific compartment for cutlery in the central galley storage unit			~

PERFORMANCE VERSION

- (only for versions A and B) • Tall anodised mast with 2 spreaders, cathedral geometry and split rigging
- Dyform standing rigging
- Performance full-batten mainsail, triradial cut,
- in grey X-Grid Mylar/Taffetas 62,68 m² / 674 sq ft • 125 % performance genoa, triradial cut, in grey X-Grid Mylar/Taffetas with uv protection
- 58,82 m² / 633 sq ft Downwind package
- Harken ball-bearing genoa lead cars and control lines lead to cockpit
- Dyneema® low-stretch halyards and sheets for main and genoa
- Hydraulic textile adjustable backstay
- Composite steering wheels

DOWNWIND PACKAGE

- Spinnaker rigging with spinlock jammers · Halyards and sheet for asymmetrical spinnaker / Code 0 (2 polyester halvards, 1 sheet and 1 tack line in dyneema®, pulleys on mast step and side decks)
- Extra Harken 46.2 ST winch to starboard on coachroof

- Extra winch handle
- Windex 15" on mast head

CONVERTIBLE COCKPIT PACKAGE

- Extending coamings convertible into lounging area
- Cushions for cockpit and sunbathing areas in Sunbrella® Oyster or Taupe
- Starboard infill cushion for I-seating area Sunbrella® Oyster or Taupe
- High transparency sprayhood Sunbrella® Oyster or Taupe in with led lighting

EXTERNAL GALLEY PACKAGE

- · Cockpit sink with hot & cold water
- Portable 12 V fridge in the cockpit table

PACK VOYAGER (only for versions A and B)

- High transparency sprayhood in Sunbrella® Oyster or Taupe with LED lighting Oyster
- Outboard engine bracket
- Releasable forestay + deck fittings
- Solar panel on coachroof with charging relay

EQUIPMENT

PACK ENTERTAINMENT AUDIO

- DVD player Fusion MS-AV755 (Radio / USB / Bluetooth...) at the chart table
- Bose[®] speakers in the saloon
- Bose[®] subwoofer
- Speakers in the cockpit

PACK ENTERTAINMENT VIDEO (only for versions A and B)

- DVD player Fusion MS-AV755 (CD / DVD / USB / Bluetooth...) at the chart
- table
- Bose® speakers in the saloon
- Bose® subwoofer
- Speakers in the cockpit
- TV LED 32" in the saloon
- DVD player Fusion MS-AV755 (CD / DVD / USB / Bluetooth...) in the forward owner's cabin
- TV LED 22" in the forward owner's cabin
- TV antenna for in mast fitting

- Full-length hull chine for improved stability and speed
- · Long waterline for better speed while sailing and under power
- L-shaped cast iron keel less exposed to seaweed and lines
- Twin rudders with self-aligning roller bearings and textile lines, to increase control and pleasure in navigation

SAILS

Standard

- · Horizontally-cut in Polyester High Strength
- · Semi-battened main sail with 3 reefs 56,60 m² / 609 Sq ft

• 125 % furling genoa with UV protection 53,60 m² / 577 Sq ft

Options

- In mast furling main sail horizontally-cut in Polyester High Strength 45,22 m² / 487 Sq ft
- · Self-tacking jib with UV protection in polyester High Strength 37,82 m² / 407 Sq ft
- Code 0 in triradial cross cut Mylar/Aramid laminate 92,50 m² / 995 Sq f with continuous line furler (requires Downwind Package)
- Code 0 in triradial cross cut Mylar/Aramid laminate for Performance mast 102,98 m² / 1108 Sq ft with continuous line furler (requires Downwind Package)

SAIL HANDLING

Standard

- Mainsheet attached to Dyneema® bridle forward of companionway, with sheets led back to the cockpit winches
- Harken genoa tracks with adjustable lead cars
- Spinlock jammers
- Coachroof winch 1 x Harken 46.2 ST to port
- Genoa winches 2 x Harken 50.2 ST winches for easy use at the helm stations
- Harken winch handle

Options

- Self-tacking jib ball bearing track on coachroof
- Electrical coachroof winch Harken 46.2 ST
- 2 x electrical primary winches Harken 50.2 ST

ARCHITECTURE

MAST AND RIGGING

Standard

- Classic aluminium mast with double
- spreaders, deck-stepped, cathedral geometry and split rigging
- Aluminium boom with rigid vang and lowered goose neck for easier handling
- Double backstay
- Genoa furler with double slot, furling line lead aft to cockpit on coach roof
- Running rigging topping lift, mainsail halvard, genoa halyard, mainsheet, genoa sheets in polyester
- Standing rigging discontinuous 1 x 19 stainless steel wire
- Asymmetrical lazy bag with integrated lazy iacks

Option

• Furling mast aluminium with double spreaders, deck-stepped, cathedral geometry and split rigging

COCKPIT

Standard

- Walk-in access to side decks, enabling to walk around the deck without crossing any steps.
- Large cockpit table with compass, cup holders, area for navigation instrument, cockpit light switch, LED lighting, bottle storage and optional portable fridge
- Teak inlay on bench seats, helms stations and transom platform
- · Fixed coaming with ideal height for comfort and safety
- Cockpit lockers: 1 on starboard side, 1 on port side (versions B, C and D only), 1 large locker on the cockpit floor that can be used for the optional generator, one liferaft locker with open access to transom platform 92 x 65 x 48 cm / 3'01" x 2'13" x 1'57
- Universal gas box, cut-off valve under the stove
- Wheels with leather wrap, space for flush mounted GPS at each helm, stainless steel handrail, cup holders
- Emergency tiller, and fitting in cockpit floor • Engine control: throttle lever at starboard
- helmstation and oriented engine panel on the cockpit table
- Large bathing platform with telescopic ladder, handrail and access step to the cockpit
- Hinged companionway doors in plexiglas
- Sliding horizontal hatch in plexiglas
- · Cockpit table with stainless steel handrails

Options

- Cockpit table with wooden leaves: replaces the standard table with all the same functions Teak inlay on cockpit floor
- Large cockpit sprayhood in Sunbrella® Oyster or Taupe, high transparency windscreen and LED cockpit lighting
- · Cockpit Bimini with stainless steel bows in Sunbrella® Oyster or Taupe, connecting fabric between Bimini and sprayhood
- Cockpit enclosure kit in Sunbrella® Oyster or Taupe, fitted on the sprayhood and bimini
- Electrical bathing platform system with remote

DECK HARDWARE

Standard

- Bow pulpit in stainless steel
- Stern pushpits in stainless steel with buoy bracket and emergency ladder
- Lifelines double level of stainless steel lifelines • Mooring cleats: 6 x aluminium
- Stainless steel handrails on coachroof (2)
- Deep anchor locker
- Electric12 V windlass 1000 W 10 mm chain
- Long fixed tinted windows along coach roof
- Fixed cockpit windows in the aft cabins (2)
- Large, fixed hull ports (6)
- Opening ports in the roof (4)
- Opening deck flush hatches (11)
- Opening ports towards cockpit in the aft cabins (1 per cabin)
- Opening ports towards side-deck in the aft cabins (1 per cabin)

Options

- Folding pulpits seating
- · Lifeline gates with removable access ladder
- Teak side-decks
- Rubrail for hull protection
- Mooring kit 6 fenders and 4 docklines Anchoring kit with Delta 20 kg / 44 lbs, 32 m /
- 104' of 10 mm chain and 45 m / 147' line
- Sunbed in Sunbrella® Oyster or Taupe on the foredeck

SAIL LOCKER

Standard

- Access via lockable deck hatch
- Access ladder in stainless steel

LIGHTING Standard

• Full LED interior lighting

ELECTRICAL

Standard

- Main 12 V electrical panel at the chart table
- 12 V Circuit for house and engine system Domestic battery bank capacity
- 3 x 115 Ah / 12 V
- Engine start battery capacity 1 x 120 Ah / 12 V
- 12 V engine alternator: 125 A · Positive and negative battery switch 12 V in the aft cabin

Options

- Lithium domestic battery bank 3 x 90 Ah / 12 V
- USB plug in each cabin
- Inverter 12 V > 220 V 2000 W enable to use 220 V appliance from the domestic battery bank
- Generator Onan 7,5 kW 230 V 2400 rpm, located at the transom

This document is non contractual and we reserve the right to modify equipment or specification without advance notice. Updated April 2018.

PLUMBING

Standard

FRESH WATER

- "Heavy-duty" water pump 19 L / 5 US gal / mn, accumulator tank for consistent water pressure
- Roto moulded tank: 400 L / 87 US gal, under the aft cabin berth
- Roto moulded tank: 240 L / 53 US gal, under the aft cabin berth
- Tank gauges (1 per tank)
- Tank manifold with selector valves
 Water boiler 40 L / 11 US gal connected to the engine and 220 V circuit
- Hot and cold cockpit shower on transom
- GREY AND BLACK WATER
- Automatic electrical shower self-activating
- Large bowl marine Toilets Black water tank 50 L / 13 US gal, with gravity drain and deck fitting (forward and port aft heads)
- Black water tank 80 L / 21 US gal, with gravity drain and deck fitting (aft starboard head)
- **BILGES DRAINAGE**
- Electric bilge pump located in bilge area with activation via switch at electrical panel
- Dual-action manual bilge pump located in the cockpit, with separate hose from primary bilge pump

GAS

• Gas leakage detector

Options

- Electric Quiet-Flush toilets, on fresh water circuit, in place of manual toilets
- Water intake in the cockpit. Enable to connect the fresh water circuit directly to the shore

ENGINE

Standard

station

cockpit

separator

Options

berth

and charger

and charger

steel exhaust fitting

and from aft cabins

• Fixed 3 blade propeller

- Latest-generation Common Rail engine with reduced emissions and consumption
- Yanmar Engine 4JH57CR Sail Drive 57 HP / 42 kW - Alternator 125 A • Engine panel oriented toward helmsman,

located on the cockpit table. Throttle at helm

• Insulation: Foam 40 mm, with fire retardant film

• Built-in muffler, air ventilation and stainless

Ventilation system extractor fan located near

the engine, benefiting from the insulation of

• Roto moulded fuel tank 240 L / 63 US gal

• Yanmar Engine 4JH80CR Sail Drive -80 HP / 59 kW - Alternator 125 A

80 HP / 59 kW - Alternator 125 A

Yanmar Engine 4JH80CR 360 Docking -

• Retractable bow thruster 6,3 kW 105 kgf (231,5 lbs) with a dedicated 12 V battery bank

 Retractable stern thruster 6,3 kW 105 kgf (231,5 lbs) with a dedicated 12 V battery bank

· Flex-o-Fold 3 blade folding propeller

• Extra fuel tank 240 L / 63 US gal, instead of a fresh water tank underneath the aft cabin

the engine room. Outlets vents at the back of

located under the aft cabin berth, fuel / water

• Access behind steps to engine compartment

Cushions in High Density foam 140 mm in the salon

• Cruisair® air conditioning working from generator

or shore power with 3 units (40000 BTU in total)

• Large domestic size, rectangular berth, 2,00 x

1,60 m / 6'6" x 5'2", with High Density Premium

locker, full height drawer, opening cabinet and LED

• Central book shelve with space for the optional TV

3 large drawers underneath the berth (2 drawers if air

• 2 Opening deck hatches, for light and ventilation

• Separate toilet compartment to port, with GRP sink

· En-suite owner's head compartment, with direct

centre of the boat for higher headroom, with its

• Electric Quiet-Flush toilets. on fresh water circuit.

• Large domestic size, rectangular berth 2,00 x

· Hanging locker storage and shelf along hull

HEADROOM

1,60 m / 6'6" x 5'2", with High Density Premium

shower, shower drain with automatic switch

dedicated opening deck hatch and plexiglas door,

access from the cabin, GRP sink furniture, drawer,

opened storage shelves, hull port allowing sea view,

opening deck hatch, indirect LED lighting, full height

mirror. Separate shower compartment located in the

above the bed and 1 in the passageway

• 2 large fixed hull ports with sliding blinds

· Deck hatches with blind and bug screens

• Lower locker with drawer, shoes storage and

• Large dressing locker to starboard with hanging

· Pushed air heating system 11000 W with outlets in



Version A Forward Owner's cabin 1 aft cabin / 2 heads

INTERIOR

Woodwork

- Fine Teak[®] interior woodwork laminated with solid wood trim, UV stabilized varnish
- Fully-upholstered hull sides and ceiling
- Ceruse light Oak laminate floorboards

Option

- · Woodwork in Alpi® grey Cedar mat finish, open-pore varnish
- Ceruse dark Oak laminate floorboards Saloon
- · Comfortable seating arrangement to starboard with view of sea though hull ports
- Hinged storage compartments under settee
- Large storage between the saloon and the companion way
- Bottles storage
- Large storage behind backrests
- Large table with 2 removable aluminium legs
- · Companionway with anti-sleep floor surface Options
- "Deluxe" folding table on telescopic legs
- Convertible berth in saloon
- · Central two-seat bench with storage

Chart table

- Large chart table with leatherette worktop, opening
- compartment for laptop computer
- Sofa in vis à vis at the chart table Book shelve
- Multiple storage for telephone, keys...
- Large storage space under electrical panel for books and other navigation equipment, storage underneath the seat
- Bicolour reading light
- · Ergonomic seat, seaworthy
- · Opening port above the chart table

Galley

- U shape galley located on port side, with view on the sea
- Counter top in Corian®, with fiddles
- Double stainless steel sinks with chrome fixtures
- Large drawer in the centre cabinet
- Soft-close, fully-extending drawers
- Sliding waste bin 26 L / 7 US gal
- Open storage behind the galley
- 2 burner stove with protective handrail
- Fridge 190 L / 50 US gal with top opening
- **Options**
- · Push up micro wave
- Extra fridge drawer 75 L / 20 US gal
- Extra freezer drawer 75 L / 20 US gal
- Dishwasher 6 place setting



Version B Forward master cabin 2 aft cabins / 2 heads

Comfort

Options

• Premium mattresses

each cabin and head

Large passageway

mattress

liahtina

• LED lighting

(Versions A and B)

• Large hanging locker to port

leatherette top finish

with manual pump

Option

Mattress battens

Aft cabins

mattress

in place of manual toilets

conditioning is selected)

• Side bed tables with leatherette

• Fully upholstered front bulkhead

• Large mirror in front of the cabin

Forward Owner's cabin



Version C 2 forward cabins 2 aft cabins / 4 heads

• LED Lighting

- LED reading lights
- 1 long fixed hull port, 1 large fixed cockpit window
- 1 opening port on coachroof, 1 opening port towards the cockpit, 1 opening port towards the side decks

Version D

2 forward cabins

3 aft cabins / 3 heads

- Blinds for each opening
- Access to tanks and technical area behind the engine • Aft head: double access, from starboard cabin and saloon, GRP sink furniture, storage with towel shelf, Teak shelf with fiddle, large roof window, opening port for light and ventilation, indirect LED lighting, shower,
- shower drain with automatic switch, water inlet valve and connector underneath the sink. large marine toilet with manual pump, hook, large mirror, shower separated with a plexiglas door on versions A and B

Workshop (Version A)

- Workshop located on port side behind the chart table. double access from the interior and from the cockpit
- LED lighting
- Large fixed hull window
- Access to the tank
- Direct access to electrical panels

Lateral storage locker Port side head (Version C)

. GRP sink furniture, storage with towel shelf, Teak shelf with fiddle, large roof window, opening port for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilets with manual pump, hook, large mirror

Portside lateral cabin (Version D)

- 2 bunk beds, hanging locker, reading LED light,
- locker underneath the inferior bed

Forward twin cabins

(Versions C and D)

- Large rectangular berth 2,00 x 1,40/0,79 m /

Forward heads (Versions C and D)

• GRP sink furniture, storage, hull port allowing sea view, opening deck hatch for light and ventilation, indirect LED lighting, shower, shower drain with automatic switch, water inlet valve and connector underneath the sink, large marine toilet with manual pump, hook

Forward cabin	1,88 m / 6'2 "	Galley	1,92 m / 6'4"
Aft cabin(s)	1,91 m / 6'3"	Forward head	1,90 m / 6'3"
Companionway	1,98 m / 6'6"	Aft head	1,93 m / 6'4"
Saloon	2,00 m / 6'7""		







furniture, storage, hull port allowing sea view, opening deck hatch, indirect LED lighting, large marine toilet

Opening deck hatch for ventilation, fixed roof windows

- 6'6" x 4'7"/2'7", with High Density Premium mattress
- Removable bulkhead between the cabins Hanging locker
- Storage underneath the berth
- LED lighting
- Opening deck hatch with ventilation
- · Large fixed hull windows with sliding blinds
- blinds and bugs screens for deck hatches